



K632-485

OEM CONTACTLESS READER/WRITER MODULE WITH ANTENNA AND RS-485 INTERFACE

Ready-to-use ISO/IEC 14443-A/B and ISO/IEC 15693 reader/writer with antenna and a standard RS-485 long-distance serial interface that can be embedded in virtually any kind of appliance

KEY FEATURES

K632-485 is dedicated to integrators who need to work with any ISO 14443-A/B or ISO 15693 cards such as Mifare, DESFire, Calypso, ICODE and more. Thanks to its asynchronous serial communication interface, K632-485 is really easy to operate from any microcontroller or host computer.


K632-485 has many features that make it the only product on the market to provide such flexibility at low cost.

- Metallic bonnets to protect from radiations
- Ferrite on antenna to protect other components from radiations
- Embedded T=CL protocol, ISO/IEC 14443 A & B (from layer 1 to 4) and ISO 15693 compliance. Able to read/write all files/sectors of Mifare, DESFire,...
- High level function set
- High speed communication

A FEW TYPICAL APPLICATIONS

- vending machine,
- card printer,
- access control gate
- enrolment station,
- and more

DETAILED VIEWS



PIN Assignments	Notes
1 /EN - Not used	Can be left unconnected
2 /FLASH - Not used	Can be left unconnected
3 Ground	
4 /RESET - 5V : normal operation 0V : module reset	Can be left unconnected
5 VCC (5V)	
6 BUS B (RS-485)	Host to module
7 BUS A (RS-485)	Module to host
8 Ground	

SPRINGCARD & PRO ACTIVE

Established in 2000, Pro Active is an innovative provider of smartcard-related solutions, and one of the leaders on the contactless-reader market.

SpringCard distributes Pro Active's contact and contactless products worldwide, under a single brand name.

HEADQUARTERS, EUROPE SPRINGCARD

13 voie la Cardon
Parc Gutenberg
91120 Palaiseau
FRANCE

Phone : +33 (0)1 64 53 20 10
sales@springcard.com

AMERICAS SPRINGCARD

6161 El Cajon Blvd
Suite B, PMB 437
San Diego, CA 92115
USA

Phone : +1 (713) 261 6746
sales-usa@springcard.com

www.springcard.com

A PRO ACTIVE BRAND

Pro Active

K632-485

OEM CONTACTLESS READER/WRITER MODULE WITH ANTENNA AND RS-485 INTERFACE



TECHNICAL SPECIFICATIONS

K632 Contactless smartcard interface

Standards	ISO/IEC 14443 A and B, T=CL ISO/IEC 15693 and 18000-3
RFID carrier	13.56 MHz
Operating distance	typical 5 cm - up to 8cm depending on card and antenna
Card baud rate	106, 212, 424 or 848 kbit/s depending on antenna
Supported cards (partial list) :	<ul style="list-style-type: none"> ▪ NXP (Philips) ICODE1, ICODE-SLI, etc ▪ Texas Instrument TagIT ▪ NXP (Philips) MIFARE Classic & UltraLight ▪ NXP (Philips) DESFIRE, SmartMX, ProX ▪ Infineon SLE66 family ▪ ST MicroElectronics SR, SRI, SRIX families ▪ HID iClass, Inside PicoTag ▪ ASK CTS256/CTS512 ▪ Calypso (CD97, CD21, GTML, etc)¹
And virtually any ISO/IEC 14443 A or B compliant smartcard, or ISO/IEC 15693 compliant RFID label	

Serial Interface

RS-485 bus	asynchronous serial communication 8 data bits, 1 stop, no flow control 38400bps
Power supply	5 V DC
Consumption	200mA typical
Connector	JST: BM08B-SRSS-TB(LF)(SN) Corresponding female connector (<i>not provided</i>) : JST: SHR-08V -S -B

Hardware specifications

Dimensions (LxWxH)	45 x 69 x 15 mm
Weight	≈ 14g
Housing	Metallic bonnets on K632 Ferrite shield on antenna

Environment and safety

Operating temperature	-20 → +70°C
Storage temperature	-40 → +85°C
MTBF	500 000 hours
CE mark	EN50082 / EN55022 class B ¹
FCC	Part 15
Other standards	RoHS

¹Safety: EN60950: 2001 ; EN 50364 : 2001, EMCEN 301 489-03 v1.4.1 ; EN 301 489-01 v1.6.1

ORDER CODES

PART #	Description
K632-485	ISO 14443-A/B and ISO 15693 OEM module with antenna and RS-485 interface

Information in this document is subject to change without notice.

Copyright © PRO ACTIVE SAS 2008, all rights reserved.
Reproduction without written permission of PRO ACTIVE is forbidden.
SPRINGCARD, PRO ACTIVE, and both logos are registered trademarks of PRO ACTIVE SAS.
All other trademarks are property of their respective owners.

PRO ACTIVE company with a capital of 227 000 €
R.C.S. EVRY B 429 665 482
N.A.F. 722 C
VAT # : FR 27 429 665 482
France

www.springcard.com

A PRO ACTIVE BRAND
**PRO
Active**