

NFC'ROLL

VERSATILE PC/SC NFC DEVICE

READER/WRITER, CARD EMULATION, PEER-TO-PEER

PC/SC NFC DEVICE

NFC'Roll connects to PC through a single USB link and 100% compliant with the PC/SC standard.

NFC'Roll supports any T=CL contactless smartcard (ISO 14443) and is able to read/write any NFC Forum Tag.

EXCLUSIVE NFC FEATURES

Its NFC peer-to-peer capability (ISO 18092), either as Initiator or as Target, is the basis of innovative applications using this exciting new technology.

And, most important, the **H512 series** is the only group of products in its market that implements the card emulation mode into the device itself.

A FEW TYPICAL APPLICATIONS

Along with its attractive look & feel and its USB interface for fast data transfer, NFC'Roll is robust and adapts to a variety of situations.

NFC'Roll is the ideal NFC peripheral to integrate into kiosks, vending machines, point-of-sales PC, card printers or issuing devices... It is perfectly adapted to :

- Event, gaming, ticketing,
- Active advertising,
- Loyalty, couponing,
- Peer-to-peer smartphone applications.

ABOUT SPRINGCARD

SpringCard products are designed and manufactured

in France, and distributed worldwide.

With 12 years of expertise in smartcards, contactless, RFID and NFC, **SpringCard** is the ideal partner to make your project a success.

HEADQUARTERS, EUROPE SPRINGCARD

13 voie la Cardon
Parc Gutenberg
91120 Palaiseau
FRANCE

Phone : +33 (0) 164 53 20 10
sales@springcard.com

AMERICAS SPRINGCARD

6161 El Cajon Blvd
Suite B, PMB 437
San Diego, CA 92115
USA

Phone : +1 (713) 261 6746
sales-usa@springcard.com

www.springcard.com

A PRO ACTIVE BRAND

**Pro
Active**

NFC'ROLL

VERSATILE PC/SC NFC DEVICE

READER/WRITER, CARD EMULATION, PEER-TO-PEER

TECHNICAL SPECIFICATIONS

Contactless smartcard interface

| | |
|---|--|
| Standards | ISO/IEC 14443 A and B, T=CL ISO/IEC 15693 and 18000-3 |
| RFID carrier | 13.56 MHz |
| Operating distance | 1 to 5 cm depending on card and on environment |
| Card baud rate | 106, 212, 424 or 848 kbps |
| NFC Forum Tag read/write | ISO/IEC 14443 : 106, 212, 424 or 848 kbit/s ISO/IEC 15693 : 26 kbit/s |
| Supported contactless smartcards (partial list) | <ul style="list-style-type: none"> ▪ NXP Mifare Classic, Mifare Plus, Desfire, SmartMX... ▪ NXP (Philips) MIFARE Classic, Plus, UltraLight ▪ NXP (Philips) DESFIRE, SmartMX, ProX ▪ NXP (Philips) ICODE1, ICODE-SLI ▪ Infineon SLE66 family ▪ Innovision Jewel, Topaz ▪ Calypso (CD97, CD21, GTML, etc), Innovatron radio protocol ▪ Texas Instrument TagIT ▪ ST MicroElectronics SR, SRI, SRIX families ▪ ATMEL CryptoRF ▪ HID iClass, Inside PicoTag ▪ ASK CTS256/CTS512 And virtually any ISO/IEC 14443 A or B compliant smartcard, or ISO/IEC 15693 compliant RFID label |
| Card emulation mode | <ul style="list-style-type: none"> ▪ On-board emulation of NFC Forum type 2 Tag and type 4 Tag, 1024kB available for NDEF data ▪ Host-based emulation mode, with T=CL |

USB PC /SC mode

| | |
|--------------------|--|
| Standard | USB 2.0 full speed interface (12 Mbps) Standard USB CCID profile |
| Power supply | Powered by USB 5V DC +/- 10%, 150mA typ. , 200mA max |
| Windows driver | 2000/XP/Vista/Seven |
| Linux, *nix driver | Supported by PCSC-lite open source stack on Linux and other Unix systems |
| API and SDK | Compliant with PC/SC version 2 specification Comprehensive SDK available free of charge, including those demo software : <ul style="list-style-type: none"> ▪ NFC peer-to-peer : basic implementation of SNEP (« NFC beam » or « NDEF push ») on top of LLCP, in both initiator and target mode ▪ NFC Forum type 2 and type 4 Tag emulation (URL, Text, SmartPoster, vCard, MIME...) ▪ PC-based card emulation mode (ISO/IEC 7816-4 cardlet running on PC) ▪ NFC Forum Tags read/write application ▪ and related applications from the PC/SC SDK |

Environment and safety

| | |
|-----------------------|---------------------------|
| Operating temperature | - 20 → + 70°C |
| Storage temperature | - 40 → + 85°C |
| MTBF | 500 000 hours |
| CE mark | EN50082 / EN55022 class B |
| Other standards | RoHS |

ORDER CODES

| PART # | Description |
|--------|----------------|
| SC2079 | NFC'Roll PC/SC |

PRECAUTIONS FOR INSTALLATION

Those devices use inductive coupling (magnetic field) to power the cards and communicate with them. Precaution must be taken to keep them far from any source of perturbation (e.g. other readers, computers...). Installing the device near a metal surface will decrease the operating distance and increase power consumption. SpringCard has a long experience. Please contact us if you need any assistance to integrate those devices.

Information in this document is subject to change without notice.

Copyright © PRO ACTIVE SAS 2010-2012, all rights reserved.
 Reproduction without written permission of PRO ACTIVE is forbidden.
 SPRINGCARD, PRO ACTIVE, and both logos are registered trademarks of PRO ACTIVE SAS.
 All other trademarks are property of their respective owners.

PRO ACTIVE company with a capital of 227 000 €
 R.C.S. EVRY B 429 665 482
 N.A.F. 722 C
 VAT # : FR 27 429 665 482
 France

www.springcard.com

A PRO ACTIVE BRAND
