

WALL-MOUNT CONTACTLESS READER

IWM-K531

IDWM-K531 is an ISO/IEC 14443 wall-mount reader for residential or corporate access control.

IDWM-K531 reads serial number from any kind of compliant contactless cards. 3 output modes are available :

- **Wiegand**, with configurable frame length,
- **Dataclock** (also known as ISO2 / Magstripe), 10 or 12 BCD digits,
- **RS-485**.

Product family

IWM-K531-485

Wall-mount contactless reader, configured with RS-485 output.

IWM-K531-WGD

Wall-mount contactless reader, configured with Wiegand output.

IWM-K531-DTC

Wall-mount contactless reader, configured with Dataclock

Benefits

K531 family has many features that make it the only product on the market to provide such flexibility at low cost.

- ✓ Full support of Philips MIFARE and DESFire leading products
- ✓ Embedded T=CL protocol, ISO/IEC 14443 A & B compliance from layer 1 to 4
- ✓ High level function set

A few applications...

- ✓ Physical access control
- ✓ ...

Development kit

Pro-Active offers a Development Kit for the IWM-531 family to assist in writing applications for almost any host microcontroller or computer. The kit includes :

- A IWM-K531 reader
- The K531 Developer's Board
- Sample MIFARE and DESFire cards
- API and sample programs (C source code), documentation
- One year access to technical support

Additional information is available on our web site, through our distributors worldwide, or by emailing us at info@pro-active.fr.



PRO ACTIVE

Parc Gutenberg
13, voie La Cardon
91120 PALAISEAU
France

www.pro-active.fr

Tel : +33 1 64 53 20 15
Fax : +33 1 64 53 20 18
e-mail : info@pro-active.fr

© Pro Active SAS 2006

Information in this document is subject to change without notice.
Reproduction without written permission of PRO ACTIVE is forbidden.
PRO ACTIVE and the PRO ACTIVE logo are registered trademarks of PRO ACTIVE SAS.
All other trademarks are property of their respective owners.