

# K632-485

OEM CONTACTLESS READER/WRITER MODULE WITH ANTENNA AND RS-485 INTERFACE

Ready-to-use ISO/IEC 14443-A/B and ISO/IEC 15693 reader/writer with antenna and a standard RS-485 long-distance serial interface that can be embedded in virtually any kind of appliance



K632-485 is dedicated to integrators who need to work with any ISO 14443-A/B or ISO 15693 cards such as Mifare, DESFire, Calypso, ICODE and more.

Thanks to its asynchronous serial communication interface, K632-485 is really easy to operate from any microcontroller or host computer.


K632-485 has many features that make it the only product on the market to provide such flexibility at low cost.

- Metallic bonnets to protect from radiations
- Ferrite on antenna to protect other components from radiations
- Embedded T=CL protocol, ISO/IEC 14443 A & B (from layer 1 to 4) and ISO 15693 compliance. Able to read/write all files/sectors of Mifare, DESFire,...
- High level function set
- High speed communication

## A FEW TYPICAL APPLICATIONS

- vending machine,
- card printer,
- access control gate
- enrollement station,
- and more

#### **DETAILED VIEWS**



	PIN Assignements	Notes
1	/EN - Not used	Can be left unconnected
2	/FLASH - Not used	Can be left unconnected
3	Ground	
4	/RESET - 5V : normal operation 0V : module reset	Can be left unconntected
5	VCC (5V)	
6	BUS B (RS-485)	Host to module
7	BUS A (RS-485)	Module to host
8	Ground	

### **SPRINGCARD & PRO ACTIVE**

Established in 2000, **Pro Active** is an innovative provider of smartcard-related solutions, and one of the leaders on the contactless-reader market.

**SpringCard** distributes **Pro Active**'s contact and contactless products worldwide, under a single brand name.

**HEADQUARTERS, EUROPE**SPRINGCARD

13 voie la Cardon Parc Gutenberg 91120 Palaiseau FRANCE

Phone: +33 (0)1 64 53 20 10 sales@springcard.com

Americas SPRINGCARD

6161 El Cajon Blvd Suite B, PMB 437 San Diego, CA 92115 USA

Phone: +1 (713) 261 6746 sales-usa@springcard.com

www.springcard.com





# K632-485

**OEM** CONTACTLESS READER/WRITER MODULE WITH ANTENNA AND RS-485 INTERFACE



# **TECHNICAL SPECIFICATIONS**

K632 Contactless smartcard interface		
Standards	ISO/IEC 14443 A and B, T=CL ISO/IEC 15693 and 18000-3	
RFID carrier	13.56 MHz	
Operating distance	typical 5 cm - up to 8cm depending on card and antenna	
Card baud rate	106, 212, 424 or 848 kbit/s depending on antenna	

#### Supported cards (partial list):

- NXP (Philips) ICODE1, ICODE-SLI, etc
- Texas Instrument TagIT
- NXP (Philips) MIFARE Classic & UltraLight
- NXP (Philips) DESFIRE, SmartMX, ProX
- Infineon SLE66 family
- ST MicroElectronics SR, SRI, SRIX families
- HID iClass, Inside PicoTag
- ASK CTS256/CTS512
- Calypso (CD97, CD21, GTML, etc)<sup>1</sup>

And virtually any ISO/IEC 14443 A or B compliant smartcard, or ISO/IEC 15693 compliant RFID label

Serial Interface		
RS-485 bus	asynchronous serial communication 8 data bits, 1 stop, no flow control 38400bps	
Power supply	5 V DC, ±10% Device must be powered by a SELV (Safety Extra Low Voltage), limited power source, in accordance with EN60950-1 : 2006	
Consumption	200mA typical	
Connector	JST: BM08B-SRSS-TB(LF)(SN) Corresponding female connector (not provided): JST: SHR-08V -S -B	
Maximum wire lenght	30 m	

Hardware specifications		
Dimensions (LxWxH)	45 x 69 x 15 mm	
Weight	≈ 14g	
Housing	Metalic bonnets on K632 Ferrite shield on antenna	

Environment and safety				
Operating temperature	-20→+70°C			
Storage temperature	-40 →+85°C			
MTBF	500 000 hours			
CE mark	EN50082 / EN55022 class B1			
FCC	Part 15			
Flammability	UL94V0			
Other standards	RoHS			

// Once mounted in the final product, the board shall not be open to operator 'Safety: EN60950: 2006

### **ORDER CODES**

PART #	Description
K632-485	ISO 14443-A/B and ISO 15693 OEM module with
	antenna and RS-485 interface

www.springcard.com

Information in this document is subject to change without notice.

Copyright © PRO ACTIVE SAS 2008, all rights reserved.
Reproduction without written permission of PRO ACTIVE is forbidden.
SPRINGCARD, PRO ACTIVE, and both logos are registered trademarks of PRO ACTIVE SAS.
All other trademarks are property of their respective owners.

PRO ACTIVE company with a capital of 227 000 € R.C.S. EVRY B 429 665 482 N.A.F. 722 C VAT #: FR 27 429 665 482

France

