


SDIO ISO14443 READER/WRITER : SP-SD01

pftc1001-ac.doc
03/01/2005
Version : AC

DETAILED VIEWS



FEATURES

Description MIFARE® contactless cards reader / writer for SDIO Now enabled handhelds, PDA, Notebook computer.
For use with operating system supporting SDIO Now.

Power supply Powered by host
Consumption 150mA

Reading range 0 cm → 2 cm (MIFARE STANDARD 1K)

Chipset RC531 Philips®

ISO compliance ISO14443-A/B

Cards type supported .. MIFARE® Classic
MIFARE® UltraLight
MIFARE® Pro / ProX
MIFARE® DESFire

Installation Plug the module in the SDIO extension slot. Plug and Play detection as a serial port under SDIO Now compatible PDA.

Implementation API implementation as a DLL for the Microsoft® Windows® CE operating system. (springprox.dll)

Connections SDIO Now

Conformity Standard CE : EN50082/EN55022 class B

Material PC
Color Black
Self-extinction UL94

Temperature range 0°C → +45°C
Dimensions L : 43mm, w : 11mm, h : 80mm
Weight 9g

Information in this document is subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of PRO ACTIVE. PRO ACTIVE and the PRO ACTIVE logo are registered trademarks of PRO ACTIVE S.A.R.L. MIFARE and Philips are registered trademarks of Philips.

DATASHEET SDIO ISO14443 READER/WRITER : SP-SD01



PRO ACTIVE
PARC GUTENBERG
13 VOIE LA CARDON
F-91120 PALAISEAU
France

phone. : +33 1 64 53 20 10
Fax : +33 1 64 53 20 18
mail : info@pro-active.fr
web : www.pro-active.fr

S.A.R.L. capital of 100 000€
R.C.S. EVRY B 429 665 482
A.P.E. 722Z
VAT #. FR27 429 665 482 00015