

ABSTRACT


Pro-Active MOD-K531-232 is an ISO14443-A OEM Module equipped with an antenna :

- Read and write access to MIFARE® cards,
- Suitable for use with DESFIRE® cards as well as with other ISO 14443-A T=CL products,
- Philips MF RC531 chipset,
- TTL (0/+5V) Serial interface allows connecting to a PC as well as to a wide range of controller devices,

Same API as Pro-Active SpringProx and CSB products, available in ANSI C through a full-featured developers kit.

The antenna, featuring :

- a ferrite shield,
- a serial TTL (0/+5V) to RS interface,



SAMPLE APPLICATIONS

- Ticketing, transportation,
- Tracking,
- Loyalty,
- Private money payment, road toll pricing,
- Physical access control

Upon request, a dedicated firmware may be developed and embedded into the MOD-531 for the highest performances in your specific application.

ORDER CODES

Pro-Active MOD-K531 OEM module with antenna :

- MOD-K531-232

Related starter kit :

- SRK-K531

Pro-Active MOD-K531 OEM module without antenna or Pro-Active MOD-K531 OEM module + square antenna with RS422 interface : see related datasheet

Information in this document is subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of PRO ACTIVE. PRO ACTIVE and the PRO ACTIVE logo are registered trademarks of PRO ACTIVE SARL. MIFARE, DESFire, PEGODA and Philips are trademarks of Philips.

DATASHEET

1/2



Pro Active
PARC GUTENBERG
13 VOIE LA CARDON
F-91120 PALAISEAU
France

Tél. : +33 164 532 010
Fax : +33 164 532 018


mail : info@pro-active.fr
web : www.pro-active.fr

S.A.R.L. capital of 100 000€
R.C.S. EVRY B 429 665 482
A.P.E. 722Z
VAT#. FR27 429 665 482 00015

MOD-K531-232 : ISO14443 OEM Reader Module with Antenna

pfte0101-aj.doc
26/04/2005
Version : AK

DETAILED VIEWS



TECHNICAL DATA

Description..... ISO14443-A OEM
Reader module with
antenna.

Order code **MOD-K531-232**

Size 69 x 45 x 13 mm

Weight 30 g

**Temperature
range** -20°C → +80°C

Power supply 5 VDC

**Power
consumption** 90mA typ. (depending
on antenna tuning and
power mode)

**Operating
distance** up to 60mm (depending
both on the tag and on
the antenna tuning)

**Serial
interface** RX/TX, CMOS-TTL (0/+5V)
38400 bauds or 115200 bps
(8 bits, 1 stop, no parity, no flow control,
other baudrates available on request)

TTL-CMOS I/Os .. Green & red LEDs (soft. controlled)
Bi-directional USER pin (soft. controlled)
Module enable / Module reset pins

Other I/Os RC531 both MFOUT & MFIN pins for
specific hardware development

Supported tag MIFARE® Standard / UltraLight (native),
MIFARE® DESFire (soft. API),
ISO14443-A tags (soft. T=CL API),

Starter Kit Pro-Active SpringProx API (ANSI C)
(featuring the whole Philips MIFARE® /
PEGODA® function set) available
separately

Information in this document is subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of PRO ACTIVE. PRO ACTIVE and the PRO ACTIVE logo are registered trademarks of PRO ACTIVE SARL. MIFARE, DESFire, PEGODA and Philips are trademarks of Philips.

DATASHEET

2/2



Pro Active
PARC GUTENBERG
13 VOIE LA CARDON
F-91120 PALAISEAU
France

Tél. : +33 164 532 010
Fax : +33 164 532 018

mail : info@pro-active.fr
web : www.pro-active.fr

S.A.R.L. capital of 100 000€
R.C.S. EVRY B 429 665 482
A.P.E. 722Z
VAT# FR27 429 665 482 00015